

Specifications	Range	Best Accuracy
<b>Model</b>		<b>UT15C</b>
LED AC/DC Voltage Indication (V)	12V	0~10V
	24V	17V±2V
	50V	35V±5V
	120V	80V±15V
	230V	165V±20V
	400V	300V±30V
	690V	510V±40V
Phase Rotation Test	Operating Voltage: 0V~690V	√
	Frequency : 50Hz~ 60Hz	
Single Lead(L2)Voltage Detection	Operating Voltage : 100V~690V	√
	Frequency: 50Hz~ 400Hz	
Continuity Test	Resistance: 0~400KΩ	√
	Beeper and LED light Indicator	
Polarity Detection	Positive & Negative	√
<b>Features</b>		
Water-Proof (IP65)		√
Auto Range		√
Work Light		√
Low Battery Indication	Short circuit two leads,LED and beeper off when the battery is low	√
LCD AC/DC Voltage Display	24V~ 690V	±(3%+8)
<b>General Characteristic</b>		
Power	1.5V Batteries (R03) X 2	
LCD Size	23 X 12mm	
Product Color	Red and Grey	
Product Net Weight	210g	
Product Size	275mm X 51mm X 30 mm	
Standard Accessories	Batteries	
Standard Individual Packing	Blister, English Manual	