

HUBER+SUHNER® DATA SHEET

Coaxial Cable: EZ_141_TP_M17



Description

SEMI RIGID, the formstable microwave cable

Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Wire	0.92 mm
Dielectric	PTFE (Polytetrafluorethyln.)		2.99 mm
Outer conductor	Copper / TP	Tube, 100 %	3.58 mm

Electrical Data

Impedance	50	Ω +/- 1
Max. operating frequency	33	GHz
Capacitance	98.1	pF/m
Velocity of signal propagation	69.5	%
Signal delay	4.8	ns/m
Insulation resistance	$\geq 1 \times 10^8$	M Ω m
Min. screening effectiveness	>120	dB (up to 18 GHz)
Max. operating voltage	1.9	kV _{rms} (at sea level)
Test voltage	5	kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	5.21	kg/100 m
Min. bending radius	static	4.78 mm

Environmental Data

Temperature range	-40 °C... + 125 °C
Installation temperature	-20 °C... + 60 °C

Ordering Information

Order as EZ_141_TP_M17

Additional Information

Remarks

(For details refer to the HUBER+SUHNER MICROWAVE CABLES AND ASSEMBLIES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group Y5 / Y12

HUBER+SUHNER® DATA SHEET

Coaxial Cable: EZ_141_TP_M17



Rev.: G

Matrix **Attenuation** [formula: $(a \cdot f^{0.5} + b \cdot f)$] **and Power CW** [formula: $(p \cdot f^{0.5})$]

Coefficients:

a=	0.32544	b=	0.03967	f _{max.} =	33	p _{at} 1GHz =	450
	Frequency		Nom. attenuation		Nom. attenuation		Max. CW power
	(GHz)		(dB / m)		(dB / ft)		(watt)
			sea level 25° C ambient temperature		sea level 25° C ambient temperature		sea level 40° C ambient temperature
	1.7		0.49		0.149		345
	3.3		0.72		0.219		248
	5.0		0.93		0.283		201
	6.6		1.10		0.335		175
	8.3		1.27		0.387		156
	9.9		1.42		0.433		143
	11.6		1.57		0.479		132
	13.2		1.71		0.521		124
	14.9		1.85		0.564		117
	16.5		1.98		0.603		111
	18.2		2.11		0.643		105
	19.8		2.23		0.680		101
	21.5		2.36		0.719		97
	23.1		2.48		0.756		94
	24.8		2.60		0.792		90
	26.4		2.72		0.829		88
	28.1		2.84		0.866		85
	29.7		2.95		0.899		83
	31.4		3.07		0.936		80
	33.0		3.18		0.969		78

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
 Phone +41 (0)71 353 41 11
 Fax +41 (0)71 353 45 90
 www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions